



service package. This means that PV system operators and installers benefit from automatic and free inverter ...

Technische Daten Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC-Anschluss Bemessungsleistung (bei 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) &#228;berlastf&#228;higkeit (bei 25&#176;C bis max. 60 Sek.)2) 4600 W 6300 W 7500 W AC Nennstrom Ausgang (bei 230 V, 50 Hz) 16 A 21,7 A 26 A AC-Nennspannung / AC-Spannungsbereich 230 V / 172,5 V bis ...

Sunny Boy 3.0 / 3.6 / 4.0 / 5.0 / 6.0; Sunny Tripower 3.0 / 4.0 / 5.0 / 6.0; Sunny Tripower 8.0 / 10.0; Sunny Central UP; ??????. ?? ?????; Sunny Boy Storage 3.7 / 5.0 / 6.0; Sunny Boy Storage 2.5; Sunny Island 4.4M / 6.0H / 8.0H; Sunny Island 4548-US / 6048-US; Sunny Central Storage UP; Sunny Central Storage 1900 / 2200 ...

Technische gegevens Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC-aansluiting Opgegeven vermogen (bij 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overbelastingcapaciteit (bij 25 &#176;C tot max. 60 s)2) 4600 W 6300 W 7500 W Nominale AC-stroom (bij 230 V, 50 Hz) 16 A 21,7 A 26 A

o SBS3.7-10 (Sunny Boy Storage 3.7) from firmware version >= 3.00.00.R o SBS5.0-10 (Sunny Boy Storage 5.0) from firmware version >= 3.00.00.R o SBS6.0-10 (Sunny Boy Storage 6.0) from firmware version >= 3.00.00.R 1.2 Target Group This document is intended for qualified persons and end users. Only qualified persons are allowed

Technical data (preliminary) Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 AC connection Rated power (at 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Overload capacity (at 25&#176;C to max. 60 sec)2) 4600 W 6300 W 7500 W AC nominal current output (at 230 V, 50 Hz) 16 A 21.7 A3) 26 A Nominal AC voltage / AC voltage range 230 V / 172.5 V to 264.5 V

Dati tecnici Sunny Boy Storage 3.7 Sunny Boy Storage 5.0 Sunny Boy Storage 6.0 Collegamento CA Potenza massima (a 230 V, 50 Hz) 3680 W 5000 W1) 6000 W1) Capacit&#224; di sovraccarico (a 25&#176;C fino a max 60 s)2) 4600 W 6300 W 7500 W Corrente nominale CA uscita (a 230 V, 50 Hz) 16 A 21,7 A 26 A

o SBS6.0-10 (Sunny Boy Storage 6.0) from firmware version >= 4.00.00.R 1.2 Target Group This document is intended for qualified persons and end users. Only qualified persons are allowed to perform the activities marked in this document with a warning symbol and the caption

Web: <https://www.edentalmart.co.za>